

Technical sheet :

# **EP 15 EASY**

---



	Technical characteristics		Metric
1.1	Manufacturer		Manitou
1.2	Model Name		EP 15 EASY
1.3	Power source		Battery
1.4	Operator type		Pedestrian
1.5	Max. capacity	Q	1500 kg
1.6	Load centre of gravity	c	600 mm
1.8	Load distance, centre of drive axle to fork	x	960 mm
1.9	Wheelbase	y	1285 mm
	<b>Weight</b>		
2.1	Service weight		220 kg
	<b>Wheels</b>		
3.1	Tyres type		Bandage
3.5.2	Number of drive wheels		1
3.2	Dimensions of front wheels		210 x 70
3.3	Dimensions of rear wheels		80 x 64
3.4	Additional wheels (dimensions)		70 x 40
3.5	Number of front wheels / rear wheels		3 / 4
3.6	Front wheel gauge	b10	404 mm
3.7	Rear wheel gauge	b11	400 mm
	<b>Dimensions</b>		
4.4	Max. lifting height	h3	120 mm
4.9	Height tiller up min.	h14	720 mm
4.9	Height tiller up max.	h14	1220 mm
4.15	Fork height in low position	h13	80 mm
4.19	Overall length	l1	1669 mm
4.20	Length to face of forks	l2	520 mm
4.21	Overall width - Single wheels	b1	568 mm
4.22	Forks section / width / length	s / e / l	50 mm x 160 mm / 1150 mm
4.25	Fork spread	b5	560 mm
4.32	Ground clearance at centre of wheelbase	m2	30 mm
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	2100 mm
4.35	Turning radius	Wa	1400 mm
	<b>Performances</b>		
5.1	Travel speed (laden / unladen)		4.50 km/h / 5 km/h
5.7	Gradeability (laden / unladen)		6 % / 15 %
5.10	Service brake		Electro magnetic
5.11	Parking brake		Handle Release
	<b>Engine</b>		
6.1	Drive motor rating S2 60 min		0.65 kW
6.2	Lift motor rating at S3 15%		0.80 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		Semi-Traction
6.4	Battery / Batteries capacity		12 V / 70 Ah
6.5	Battery weight (+/- 5%)		50 kg
	<b>Miscellaneous</b>		
8.1	Type of drive control		AC
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 70 dB(A)

## EP 15 EASY - Dimensional drawing

 EP 15 EASY  EP 15 EASY



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

[www.manitou.com](http://www.manitou.com)



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes