

Technical sheet :

ES 410 ET



| | Technical characteristics | | Metric |
|-------|---|-----------|--------------------------|
| 1.1 | Manufacturer | | Manitou |
| 1.2 | Model Name | | ES 410 ET |
| 1.3 | Power source | | Battery |
| 1.4 | Operator type | | Pedestrian |
| 1.5 | Max. capacity | Q | 1000 kg |
| 1.6 | Load centre of gravity | c | 600 mm |
| 1.8 | Distance from Load backrest to center of rear axle | x | 720 mm |
| 1.9 | Wheelbase | y | 1245 mm |
| | Weight | | |
| 2.1 | Service weight | | 870 kg |
| 2.2 | Weight on front axle (laden) / rear axle (laden) | | 709 kg / 1161 kg |
| 2.3 | Weight on front axle (Unladen) / rear axle (Unladen) | | 609 kg / 261 kg |
| | Wheels | | |
| 3.1 | Tyres type | | Polyurethane |
| 3.5.2 | Number of drive wheels / Size of drive wheels | | 1x230x70 |
| 3.3 | Number of load wheels / Size of load wheels | | 2 / 125x50 |
| 3.4 | Number of stabilizer wheels / Size of the stabilizer wheels | | 1 / 125x50 |
| 3.5 | Number of front wheels / rear wheels | | 2 / 2 |
| 3.6 | Front wheel gauge | b10 | 517 mm |
| 3.7 | Rear wheel gauge | b11 | 380 mm |
| | Dimensions | | |
| 4.15 | Fork height in low position | h13 | 85 mm |
| 4.19 | Overall length | l1 | 1870 mm |
| 4.20 | Length to face of forks | l2 | 720 mm |
| 4.21 | Overall width | b1 | 800 mm |
| 4.22 | Forks section / width / length | s / e / l | 60 mm / 180 mm / 1150 mm |
| 4.24 | Fork carriage width | b3 | 680 mm |
| 4.31 | Ground clearance below mast | m1 | 35 mm |
| 4.32 | Ground clearance at centre of wheelbase | m2 | 20 mm |
| 4.35 | Turning radius | Wa | 1400 mm |
| | Performances | | |
| 5.1 | Travel speed (laden / unladen) | | 5.80 km/h / 6 km/h |
| 5.2 | Lifting speed (laden / unladen) | | 0.24 m/s / 0.14 m/s |
| 5.3 | Lowering speed (laden / unladen) | | 0.20 m/s / 0.30 m/s |
| 5.10 | Service brake | | Electro magnetic |
| | Engine | | |
| 6.1 | Drive motor rating S2 60 min | | 1.20 kW |
| 6.2 | Lift motor rating at S3 15% | | 3 kW |
| 6.4 | Battery / Batteries capacity | | 24 V / 160 Ah |
| 6.5 | Battery weight (+/- 5%) | | 150 kg |
| | Miscellaneous | | |
| 8.1 | Type of drive control | | AC |
| 8.4 | Sound level at the driver's ear according to DIN 12 053 | | 65 dB(A) |

ES 410 ET - Dimensional drawing



Characteristics of masts and residual capacities

| Central Cylinder Duplex | | CCD 26 | CCD 29 | CCD 34 |
|---|----|--------|--------|--------|
| h3 - Mast lifting height * | mm | 2940 | 2940 | 2940 |
| h2 - Mast free lift * | mm | 140 | 140 | 140 |
| h1 - Mast height lowered | mm | 1940 | 1940 | 1940 |
| h4 - Mast height extended | mm | 3365 | 3365 | 3365 |
| Residual capacity without attachment (Industrial load chart) | kg | 1000 | 1000 | 850 |

| Central Cylinder Simplex | | CCS 15 | CCS 17 |
|---|----|--------|--------|
| h3 - Mast lifting height * | mm | 2940 | 2940 |
| h2 - Mast free lift * | mm | 140 | 140 |
| h1 - Mast height lowered | mm | 1940 | 1940 |
| h4 - Mast height extended | mm | 3365 | 3365 |
| Residual capacity without attachment (Industrial load chart) | kg | 1000 | 1000 |



Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes