



Technical sheet :

EP 22 PFR 9



	Technical characteristics		Metric
1.1	Manufacturer		Manitou
1.2	Model Name		EP 22 PFR 9
1.3	Power source		Battery
1.4	Operator type		Carried
1.5	Max. capacity	Q	2200 kg
1.6	Load centre of gravity	c	600 mm
1.8	Load distance, centre of drive axle to fork	x	894 mm
1.9	Wheelbase	y	1496 mm
	Weight		
2.1	Service weight		630 kg
2.2	Weight on front axle (laden) / rear axle (laden)		1247 kg / 1583 kg
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		425 kg / 205 kg
	Wheels		
3.1	Tyres type		Bandage
3.5.2	Number of drive wheels		1
3.2	Dimensions of front wheels		1 x (230 x 75)
3.3	Dimensions of rear wheels		4 x (82 x 68)
3.4	Additional wheels (dimensions)		2 x (120 x 50)
3.5	Number of front wheels / rear wheels		3 / 4
3.6	Front wheel gauge	b10	435 mm
3.7	Rear wheel gauge	b11	365 mm
	Dimensions		
4.4	Max. lifting height	h3	125 mm
4.9	Height tiller up min.	h14	1024 mm
4.9	Height tiller up max.	h14	1276 mm
4.15	Fork height in low position	h13	85 mm
4.19	Overall length	l1	1855 mm
4.20	Length to face of forks	l2	705 mm
4.21	Overall width - Single wheels	b1	688 mm
4.21	Overall width	b1	688 mm
4.22	Forks section / width / length	s / e / l	45 mm x 175 mm / 1150 mm
4.25	Fork spread	b5	540 mm
4.32	Ground clearance at centre of wheelbase	m2	40 mm
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	2685 mm
4.35	Turning radius	Wa	2250 mm
	Performances		
5.1	Travel speed (laden / unladen)		8.50 km/h / 9 km/h
5.2	Lifting speed (laden / unladen)		0.02 m/s / 0.03 m/s
5.3	Lowering speed (laden / unladen)		0.05 m/s / 0.04 m/s
5.7	Gradeability (laden / unladen)		12 % / 20 %
5.10	Service brake		Electro magnetic
5.11	Parking brake		Handle Release
	Engine		
6.1	Drive motor rating S2 60 min		1.70 kW
6.2	Lift motor rating at S3 15%		2 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		No
6.4	Battery / Batteries capacity		24 V / 270 Ah
6.5	Battery weight (+/- 5%)		245 kg
	Miscellaneous		
8.1	Type of drive control		AC
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 70 dB(A)
	Vibration on hands/arms		2.50 m/s ²

EP 22 PFR 9 - Dimensional drawing





Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes